

# Declaration of Performance

## JORDAHL® brickwork support brackets JVA+ and JVAeco+

### 1. Unique identification code of the product-type:

JORDAHL® brickwork support brackets JVA+ and JVAeco+

### 2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

3.5, 4.5, 7.0, 9.0, 10.5 and 13.5 according to marking on product

### 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Generic type and use** Device attached to structural elements, supporting faced brickwork

**Material** Stainless steel 1.4062, 1.4162, 1.4362 according to EN 10088 for medium corrosion exposure. e.g. curtain walls

**Loading** Static and quasi-static loading

### 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

PohlCon GmbH, Nobelstraße 51, 12057 Berlin, Germany

### 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

–

### 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

### 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body IFBT – 1109 – tested as a testing laboratory the product under System 3 and issued the certificate of constancy of performance – 1109-CPD-2296 – for the product.

### 8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

–

### 9. Declared performance

Essential characteristics	Performance
Load bearing capacity	Type number 3,5: 3500 N, Type number 4,5: 4500 N, Type number 7,0: 7000 N, Type number 9,0: 9000 N, Type number 10,5: 10500 N, Type number 13,5: 13500 N
Deflection	< 2 mm at 1/3 of capacity
Durability	Material reference: 23
Dangerous substances	NPD
Harmonized technical specification	EN 845-1

### 10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.



Daniela Veit, Managing Director



i.V. Christoph Mahrenholtz, Head of Engineering  
Berlin, 01.03.2022

[\\*\) Weitere Informationen](http://qr.jordahl-group.com/en/jvaeco) [qr.jordahl-group.com/en/jvaeco](http://qr.jordahl-group.com/en/jvaeco)